

# WSV10H200S, WSAT10H200S, WSCT10H200S, WSR10H200S-HAF

## Silicon Epitaxial Trench Schottky Barrier Rectifiers


Reverse Voltage - 200 V  
Forward Current - 10 A

### Features

- Low forward voltage drop, low power losses
- High efficiency operation
- Halogen and Antimony Free(HAF), RoHS compliant

### Applications

- For use in high frequency converters
- Switching power supplies



### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	200	V
Average Rectified Forward Current	$I_{F(AV)}$	10	A
Peak Forward Surge Current 8.3 ms Single half sine-wave Superimposed on Rated Load (JEDEC Method)	$I_{FSM}$	160	A
Junction Temperature	$T_j$	175	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 55 to + 150	$^\circ\text{C}$

### Thermal Characteristics (at $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	WSV10 H200S	WSAT10 H200S	WSCT10 H200S	WSR10 H200S	Unit
Typical Thermal Resistance-Junction to Case	$R_{\theta JC}$	3.5	4.5	3	4.5	$^\circ\text{C/W}$

### Electrical Characteristics (at $T_a = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Max.	Unit
Forward Voltage at $I_R = 50 \mu\text{A}$	$V_{BR}$	200	-	V
Forward Voltage at $I_F = 2 \text{ A}$	$V_F$	-	0.72	V
at $I_F = 3 \text{ A}$		-	0.76	
at $I_F = 5 \text{ A}$		-	0.8	
at $I_F = 10 \text{ A}$		-	0.87	
at $I_F = 15 \text{ A}$		-	0.91	
at $I_F = 20 \text{ A}$		-	0.97	
DC Reverse Current at $V_R = 200 \text{ V}$	$I_R$	-	50	$\mu\text{A}$

Winning  
Team  
互創國際

# WSV10H200S,WSAT10H200S,WSCT10H200S,WSR10H200S-HAF

## Electrical Characteristics Curves

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Reverse Current vs. Reverse Voltage




Fig. 3 Junction Capacitance vs. Reverse Voltage






Fig. 4 Thermal Resistance




# WSV10H200S, WSAT10H200S, WSCT10H200S, WSR10H200S-HAF

## Package Outline Dimensions (Units: mm)



## Recommended Soldering Footprint




## Packing information

Package	Type	Carton Quantity	Box Quantity	Base Quantity	Delivery Mode
TO-263	WSV10H200S	5 K / Carton	1 K / Box	50 pcs / Tube	Tube
TO-220F	WSAT10H200S	5 K / Carton	1 K / Box	50 pcs / Tube	Tube
TO-220FB	WSCT10H200S	5 K / Carton	1 K / Box	50 pcs / Tube	Tube
TO-252	WSR10H200S	25 K / Carton	5 K / Box	2.5 K / Reel	Reel

## Marking information

"XXXXXXXXXX" = Part No.  
 "\*\*\*\*\*" = Date Code Marking  
 Font type: Arial



**Winning Team**  
 互創國際